

Non Destructive Testing & Material Evaluation Portable Ultrasonic Flaw Detectors



Features :-

- A bright High Resolution TFT Display.
- Light weight, easy to operate.
- DAC with Alarm.
- Rectified as well as RF Display.
- Freeze Mode.
- Dual Gate.

SPECIFICATION FOR ULTRASONIC FLAW DETECTOR TS2028H

Test Range	: 0 to 10 meters
Frequency Range	: 0.5 - 10 Mhz.
Pulser Type	: Spike.
Gain	: 0 to 110 in db in the steps of 2db,6db & 20db
Sensitivity	: 140 ± 3 db
Suppression	: 0 to 100% height of the L.C.D screen
Linearity	: Linear display of echoes horizontal and Vertical with deviation $\pm 1\%$
Gain Accuracy	: Calibrated to ± 1 db

Delay	: 0-500 mm in steel
PRF	: Coupled with test ranges 2KHz to 125 KHz
Voltage Supply	: 230 V / 50 hz or by NiCd cells
Acceptable Ambient Temperature	: 0 to 55 degree C
Gate (Monitor)	: Two Monitor
Monitor Threshold	: 25% to 100% of scale height
Display	: Colour TFT Display (112 x 98mm), Colour selection as per pre-defined programme.
Material Velocity	: 1000-9999 m/s adjustable, 2 fixed values (3230 / 5920).
Refracted Angle	: Variable 0°- 90°
Pulser Energy	: Low 200V / High 400 V.
Damping	: 100 and 400 Ohms.
Rectification	: RF full wave, rectified (+ ve).
Analog Bandwidth	: 0.5 to 10 MHz.

NOTE: Technical specifications are subject to change without prior notice, due to continuous upgradation.

CONTACTS

Factory

Gandhinagar

Tel: 079-23287452 / 23287454 Fax: 23287555

Exports

Tel: 022 42111802
Email: export@rooptelsonic.com
adityatrivedi@rooptelsonic.com

Thailand

754/191 Soi Punnavithi 22,
Sukhumvit 101, Bangjak,
Prakhanong, Bangkok 10260
Thailand.
Tel: +66 (0) 2741 3835
Fax: +66 (0) 2741 8915

Email: thailand@rooptelsonic.com

Malaysia

10, Jalan Jasmin 6/KS6,
Bandar Botanic,
41200, Klang, Selangor Darul
Ehsan, Malaysia.
Tel: 6019-352 6042

Email: mashadani@telsonic.com.my

Vietnam

Lot 10, Phuc Loi, Long Bien,
Hanoi City 100.803 Vietnam
Tel : 84/ 4 3872 7130;
Tel : 84/ 4 3872 7131
Tel : 84/ 983 96 9798
Www.vinasonic.vn

Email: Telsonic@vnn.vn



An Indo-Swiss joint venture



A/41, Nandkishore Industrial Estate, Off Mahakali Caves Road, Andheri (E), Mumbai - 400 093.

Tel: 022-26870990/0981/1034, 42111500 Fax : 42111505/26870004 E-mail: sales@rooptelsonic.com Web: www.rooptelsonic.com