

High Efficiency ECO Series Generators

For Cleaning System

ULTRASONIC CLEANING SYSTEM ECO[®]

The success of a large cleaning system depends mainly on Ultrasonic Generators and Transducers. We offer efficient ECO-Generators. Due to their compact design they require less space and are usable in a raw environment. This is allowed by an indirect cooling which ensures that the cooling air does not get in contact with the electronic components.

The inputs and outputs are specially constructed for machine builders and offer all possibilities of external controls. Due to the process control, it is possible to achieve special generator settings with an interface adapter and a terminal.

The generators all-purpose housing allows the application as a table top version in 19" switchboards or DIN-rails. The ECO's power spectrum includes 750 W to 1500 W for tube resonators and immersing transducers.

TECHNICAL DATA

Frequency	20, 25, 30, 40 kHz + 1 kHz (automatic control)
Power per Module	750 / 1000 / 1500 Watts
Dimensions table top version (B x L x T)	105 x 155 x 390 mm
Options	Mounting brackets (wall and control cabinet mounting kit) Service connector RS-232 (monitoring control interface)

GENERATORS



- ★ Suitable for large output powers
- ★ Designed for tube resonators, immersing transducers and transducer plate fitted to tanks
- ★ Optional communication via RS-232 interface
- ★ Three free programmable relay outputs
- ★ Five DC-isolated 24V inputs, for external power setting for instance
- ★ Over-temperature and over-current turn off
- ★ Protected against short-circuit and no-load operation
- ★ Coefficient of efficiency >90%
- ★ Fully automatic control and monitoring
- ★ Table Top housing, 19" Rack mounted version, DIN-rail-mounting or wall fastening

TUBE RESONATORS



TUBE RESONATOR

This novel design of transducer in tubular form ensures ultrasonics in all 360° and ease in retrofitting in existing system. This is available in various frequencies and different mounting lengths.

- ★ Very intensive and homogeneous sound field due to 360° radiation
- ★ Low weight and volume allows a mounting in confined spaces
- ★ Possible to mount in pressure and vacuum tanks
- ★ No dirt deposit onto the radiation surface
- ★ Ideal for retrofit in existing tanks
- ★ Multiple application, thanks to different mounting lengths
- ★ Low power consumption due to high coefficient of efficiency (>92%)
- ★ Suitable for large output powers

IMMERSIBLE BOX

This is available in different sizes, with different output power.



IMMERSIBLE BOX

CONTACTS

Head Office

Mumbai

Tel: 2687 0990/1034. Fax 022-2687 0004

Our Branch Offices

New Delhi

Tel: 011-22433703 / 22422404 Extn: 207

Chennai

Tel: 044-24354383

Factory

Gandhinagar

Tel: 079-23232159 / 23223002 Fax: 23224803

Kolkata

Tel: 033-2454 9105 / 2454 9106



A/41, Nandkishore Industrial Estate, Off Mahakali Caves Road, Andheri (E), Mumbai - 400 093.

E-mail: rooptelsonic@vsnl.com, Web: www.rooptelsonic.com